Towards Optimal Orders for Entanglement Swapping in Path Graphs: A Greedy Approach

Van Sy Mai *CTL, NIST* Gaithersburg, MD USA vansy.mai@nist.gov Abderrahim Amlou *CTL, NIST* Gaithersburg, MD USA abderrahim.amlou@nist.gov Amar Abane *CTL, NIST* Gaithersburg, MD USA amar.abane@nist.gov Abdella Battou *CTL, NIST* Gaithersburg, MD USA abdella.battou@nist.gov

Abstract—This paper considers the problem of finding an optimal order for entanglement swapping in a heterogeneous path of quantum repeaters so as to maximize the path throughput defined as the delivery rate of end-to-end entanglements. The primary difficulty in addressing this problem lies in the vast array of possible swapping orders for large paths and the complexity of the expected throughput, which depends on the attributes of each node and edge along the path, as well as the order of swapping. To cope with these issues, we first propose simple approximations in estimating the swapping outcome between two entanglement distributions that can run in constant time, thereby providing an efficient approach for evaluating and comparing different swapping orders, allowing us to solve the problem exactly for small paths. Second, as the number of possible orders grows exponentially with the number of repeaters in the path, we develop an efficient heuristic based on the greedy selection of nodes to sequentially perform swaps according to their swapping scores, defined as the expected number of entanglements resulting from their swaps. The scores are local but dynamic in the sense that they depend not just on the entanglement distributions available on the path but also on prior swapping decisions. Finally, we illustrate the efficiency and effectiveness of our proposed model and approach through extensive experimentation conducted using a general quantum network simulator.

I. INTRODUCTION

Entanglement swapping is a fundamental operation in quantum networks that extends entanglement over long distances by linking shorter entangled segments through intermediate nodes (i.e., repeaters) [3], [8]. The efficiency of this process depends heavily on the swapping policy, which determines the rules in making swapping decisions along a path [7], [6].

Swapping approaches can be distinguished by the knowledge required to make a swapping decision at a node [1]. With unheralded swapping, nodes locally perform swapping without awaiting the outcomes of other nodes [13]. In this policy, nodes carry out swapping operations independently and in parallel once adjacent quantum links are available. Although simple, unheralded swapping may result in lower success probabilities and inefficient resource utilization due to the lack of coordination among nodes. In contrast, heralded swapping instructs nodes to make swapping decisions based on the outcomes of other nodes, giving rise to a swapping *order* for the path in each end-to-end (E2E) entanglement distribution. This improves the E2E entanglement rate and fidelity, at the expense of increasing the amount of classical signaling [11].

Heralded swapping policies can be categorized as either static or dynamic. Static policies predefine the swapping order before execution [18], ensuring predictable operation but providing limited optimization to maximize throughput, especially in heterogeneous networks where link capacities and entanglement success rates vary. Dynamic policies, in contrast, determine swapping decisions (thus, swapping order) on a path basis and in real time based on the availability of entanglement (e.g., along a path) [12]. By dynamically adapting to network conditions, such policies can lead to optimal swapping decisions but introduce additional signaling overhead, latency, and coordination complexity.

A key challenge in optimizing entanglement swapping arises from the heterogeneity of quantum networks, where quantum channels can have different capacities and lengths, leading to different entanglement generation success probabilities [14]. Unlike many existing works that assume unit-capacity quantum channels or uniform entanglement success probabilities along paths, we consider quantum channels with non-uniform capacities greater than one, where multiple entanglements can be stored and swapped. Additionally, we assume that swapping at a node can be performed between any pair of locally held qubits, allowing for more flexible swapping strategies.

In this work, we focus on static swapping policies and propose heuristics for efficiently evaluating and comparing different swapping orders. Specifically, to address the computational challenges associated with computing the expected throughput of a path with high link capacities, we introduce an approximation technique that significantly reduces complexity while maintaining high accuracy. Then to avoid searching in an exponentially vast array of possible swapping orders, we develop a greedy selection algorithm that assigns a swapping score to each node, prioritizing swaps based on expected entanglement throughput. Our approach is designed to scale efficiently to paths with large capacities, making it particularly suitable for heterogeneous quantum networks. We also demonstrate an application of our approach in optimizing

Certain commercial entities, equipment, or materials may be identified in this document in order to describe an experimental procedure or concept adequately. Such identification is not intended to imply recommendation or endorsement by the National Institute of Standards and Technology, nor is it intended to imply that the entities, materials, or equipment are necessarily the best available for the purpose.

not just swapping orders but also memory allocation for each link in a path. Through extensive simulations, we demonstrate that our heuristic achieves higher (and often the highest) entanglement generation rates than conventional static policies while maintaining efficient resource utilization.

The rest of this paper is organized as follows. We briefly described related work in Section II. The problem formulation is given in Section III, followed by our main results in Section IV. Section V presents numerical results to illustrate the usefulness of our approach. Finally, conclusions are given in Section VI.

Notation: $\mathbb{E}[X]$ denotes the expected its value of a random variable X. \mathcal{B} and \mathcal{N} denote Binomial and Normal distributions, respectively. We represent vectors using bold letters.

II. RELATED WORK

Swapping can be classified into two main categories: memory-less and memory-based (or synchronous and asynchronous protocols, respectively). In memory-less swapping, entanglements along a path must be generated simultaneously, requiring strict synchronization across routers. This approach yields high fidelity but suffers from low generation rates due to the need to restart the entire process upon any failure.

In contrast, memory-based swapping allows qubits to be stored and swapped asynchronously, making the process more resilient to failures, thereby increasing the overall throughput and efficiency [6]. Several policies exist in this category:

• *Sequential:* Nodes perform swapping in a linear order, e.g., left to right. While simple, this method incurs high wait times and classical signaling due to its sequential nature [15].

• *Doubling:* Nodes swap following a binary tree structure. This approach achieves logarithmic steps, optimizing the generation rate for homogeneous chains [4], [21].

• *Parallel:* All nodes perform swapping simultaneously in a single step, but the process restarts if any entanglement or swapping fails, leading to lower generation rates [7].

• *Ad-hoc:* Swapping is based on the local or quasi-local state of the path, leading to dynamic order execution. Fully-local policies, such as random swap-as-soon-as-possible (swap-asap), where nodes execute swapping based only on locally available entanglements, are commonly used [9], [13]. The work in [11] proposes quasi-local policies, such as Strongest Neighbor and Farthest Neighbor swap-asap, where nodes make decisions using knowledge of their immediate neighbors, striking a balance between fully-local and global path knowledge.

• *Heuristic:* Swapping orders are optimized based on throughput or latency using combinatorial algorithms including dynamic programming and reinforcement learning (RL), which adapt dynamically to link states [10], [15], [7], [12].

Most swapping policies need the routers to be in agreement on a particular order to perform swapping along the path. Since these orders are predefined or computed once, they can be considered as *static* swapping policies. Ad-hoc and certain heuristic policies can be seen as *dynamic* swapping, where the swapping sequence is a stochastic process driven by the randomness of entanglement availability and swapping. Swapping instructions for an ad-hoc policy can be as simple as satisfying certain local conditions, while RL-based swapping policies as in [12] must rely on non-local instructions (e.g., from a central entity) because swapping actions in each step depend on the current state of the whole path.

The main challenge in finding an optimal swapping order is that it is inherently combinatoric in addition to the computational challenges associated with determining the expected throughput, making exact computation impractical for long paths. Existing works typically fix swapping policies or assume static swapping times [18], [5], [17]. Some research adopts different formulations, like expected generation latency and uses dynamic programming for optimal swapping tree selection [10], [12].

In this work, we develop efficient heuristics for evaluating and comparing static swapping orders. We propose a greedy algorithm and a practical method to quickly assess and select good policies tailored to specific network constraints.

III. PROBLEM FORMULATION

A. Entanglement Swapping on a Path

In this subsection, we describe a general quantum routing model adapted from previous work in [17], [18], [6], [7], [1], where time is loosely synchronized and slotted, and within each time slot, there are two main phases, namely external phase for generating elementary entanglements and internal phase for establishing long-distance entanglements via quantum swapping, which includes swapping time and all necessary classical signaling latency. (We will demonstrate in Section V below how our model can still be used in the asynchronous and discrete-event cases.) We do not require these phases to be non-overlapped, i.e., entanglement generation can continue in the background as long as memory is available, but assume that the duration of the internal phase is negligible compared to that the external phase. Here, the assumption is that the duration of a time slot is chosen appropriately depending on physical hardware so that established entanglements can be used within one time slot.¹ In this work, we focus on the main idea and key elements of entanglement swapping in a path and do not consider fidelity issue and purification; we leave them for future work on entanglement routing in a general network.

a) Topology: Consider a path graph with the set of nodes $\mathcal{V} = \{0, 1, \ldots, n\}$ and the set of edges $\mathcal{E} = \{(0, 1), (1, 2), \ldots, (n - 1, n)\}$. Here, each node $u \in \mathcal{V}$ is a quantum node, equipped with a limited number of qubits to create Bell pairs. All nodes are connected via a classical

¹The actual duration of a time slot is actually an important factor that affects quantity/quality of entanglements since it is related to the entanglement generation rates as well as coherence times of quantum memories. It is also crucial for practical implementations of routing algorithms because near-term quantum communication relies on heralded entanglement generation that requires classical signaling between quantum nodes. For simplicity, we assume in this section that the duration of a time slot is sufficient for carrying out necessary operations of a routing algorithm before entanglements decohere, including processing time of routing protocols, entanglement generation/swapping and signaling, and consumption by applications. We will analyze the effect of coherence time in choosing an time slot for our model in Section V below.

network. An edge $(u, v) \in \mathcal{E}$ existing between two nodes u and v means that they share one or more quantum channels allowing for qubits transmission. We refer to the graph \mathcal{G} formed by the nodes and physical channels as the physical topology of the quantum network.

b) Quantum Link: Since quantum channels are inherently lossy, each attempt to create an entanglement via a channel only succeeds with a certain probability. For a channel over an edge (u, v), this probability is proportional to $e^{-\alpha L_{uv}}$, where L_{uv} is the physical length of the channel and α is a constant depending on the physical media (e.g., optical fiber, free space). If an attempt succeeds, the two nodes u and vshare an elementary entanglement pair, i.e., there is a quantum *link* between u and v. Let us denote by p_{uv} the overall success probability of a quantum link, taking into account efficiencies of entanglement sources and detectors, and the number of attempts allowed in one phase within a time slot. Here, for simplicity, we can assume that for each edge $(u, v) \in \mathcal{E}$ the physical media is the same for all channels connecting u and v, and thus the success probability p_{uv} is the same for all channels between u and v.

Each edge $(u, v) \in \mathcal{E}$ is then characterized by a *capacity*, denoted by c_{uv} , representing the maximum number of quantum links that can be established within a time slot. In general, the capacity c_{uv} can be different from the number of physical channels, taking into account different multiplexing modes (including time, space, and wavelength multiplexing) and the limited numbers of qubits at u and v. The special case with $c_{uv} = 1$ has been studied extensively in the literature. It is important to note that, unlike many previous works [17], [18], [7], we do not assume qubit-channel binding conditions (i.e., each qubit is assigned to at most one channel and each end node of a quantum channel is assigned at most one qubit).

Let E_{uv} denote the number of elementary entanglements generated on edge (u, v) (as the result of the external phase) before swapping.² Clearly, E_{uv} can be modeled as a random variable (r.v.) following a Binomial distribution as follows:

$$E_{uv} \sim \mathcal{B}(c_{uv}, p_{uv})$$

i.e., the probability of having exactly k entanglements on edge (u, v) for $k = 0, 1, \ldots c_{uv}$ in each time slot is given by

$$p_k(u,v) := \Pr(E_{uv} = k) = \binom{c_{uv}}{k} p_{uv}^k (1 - p_{uv})^{c_{uv} - k}.$$
 (1)

c) Swapping in a Path: A (quantum) path between two nodes is simply a concatenation of contiguous edges with positive capacities, where an end-to-end entanglement can be established by creating quantum links on all the edges and then performing entanglement swapping at the intermediate nodes, i.e., the internal phase.

In particular, to combine two adjacent entanglements, say (u, v) and (v, w), node v attempts swapping on its corresponding local qubits which may succeed with a probability q_v resulting in an (u, w) entanglement. More generally,

suppose that node v has l(u, v)-entanglements and r(v, w)entanglements. Then, assuming that swapping operations can be performed between any pair of qubits in memories of a node, node v can attempt at most $\min\{l, r\}$ swaps to establish multiple entanglements between u and w. As a result, by swapping at all the intermediate nodes, elementary entanglements are consumed to generate end-to-end entanglements. There are different swapping policies resulting in different swapping schemes as discussed in Section II. In this paper, we will focus on the case of heralded swapping policies.

With slight abuse of notation, we define the capacity c_{xy} of a subpath from x to y as

$$c_{xy} = \min_{x < l \le y} c_{l-1,l}.$$
(2)

We also let $p_i(x, y)$ and $p_j(y, z)$ denote the probabilities of having exactly i(x, y)-entanglements and j(y, z)entanglements prior to swapping at node y, where $i \le c_{xy}, j \le c_{yz}$, and x, y and z need not be adjacent nodes. Conditioned on i(x, y)-entanglements and j(y, z)-entanglements (and all previous successful swaps), there are at most $m = \min\{i, j\}$ possible swaps at node y, again assuming that swapping can be performed between any pair of qubits in memory. Then

$$E_{xz}|E_{xy}, E_{yz} \sim \mathcal{B}\big(\min\{E_{xy}, E_{yz}\}, q_y\big). \tag{3}$$

Thus the conditional probability of having exactly k successful (x, z) entanglements is simply

$$\Pr(E_{xz} = k | E_{xy} = i, E_{yz} = j) = \binom{m}{k} q_v^k (1 - q_v)^{m-k}$$
(4)

for $k = 0, 1, ..., m = \min\{i, j\}$. As a result, the probability of having exactly k(x, z)-entanglements $p_k(x, z)$ after at most c_{xz} swapping attempts at node y can be computed as

$$\sum_{i=k}^{c_{xy}} \sum_{j=k}^{c_{yz}} p_i(x,y) p_j(y,z) \binom{\min\{i,j\}}{k} q_y^k (1-q_y)^{\min\{i,j\}-k}$$
(5)
or $k = 1, \dots c_{xz}$ and $p_0(x,z) = 1 - \sum_{k=1}^{c_{xz}} p_k(x,z)$. This

for $k = 1, \ldots c_{xz}$ and $p_0(x, z) = 1 - \sum_{k=1}^{c_{xz}} p_k(x, z)$. This allows us to find probabilities of long distance entanglements $p_k(0, n)$ for any swapping sequence.

d) Path Throughput: As shown above, given a path with certain link entanglement distributions and node swapping probabilities, E2E entanglements can be established by swapping at all intermediate nodes, the results of which depend on how swapping operations are carried out.

Let \mathcal{O} be a swapping order and $p_k^{\mathcal{O}}(0, n)$ denote the corresponding probability of having exactly k end-to-end entanglement. Then the expected number of end-to-end entanglements $\mathbb{E}[E_{0n}]$ in one time slot after swapping at all nodes is computed as follows

$$\operatorname{ENT}(\mathcal{O}) := \sum_{k=1}^{c_{0,n}} k \times p_k^{\mathcal{O}}(0,n),$$
(6)

where $c_{0,n}$ is also known as the (minimum) width of the path. Here we have to assume that the age of E2E entanglements after both (external and internal) phases is strictly within the

 $^{^{2}}$ In fact, one should think of E_{uv} as the entanglement generate rate since it is defined according to a time slot.

coherence time of memory, denoted by $T_{\rm cohere}$. As a result, ENT will be proportional to the path throughput (measured in the number of delivered E2E entanglements per second) and will be used as our metric below. We conclude this subsection with an example demonstrating how orders affect throughput.

Example 1: Consider a network with 5 nodes in Fig. 1 with elementary entanglement success rates $p_{i,i+1} = 0.2, \forall i = 0, \ldots, 3$, swapping success rates $q_j = 0.5$ for j = 1, 2, 3, and the link capacities are $c_{01} = 100, c_{12} = 200, c_{23} = 300$ and $c_{34} = 400$. We have ENT([3, 2, 1]) = 7.16 is the highest throughput. Other orders are ENT([1, 3, 2]) = ENT([3, 1, 2]) = 5, ENT([2, 3, 1]) = 4.97, ENT([2, 1, 3]) = 4.42, and ENT([1, 2, 3]) = 2.5.



Fig. 1: Example of a path with 5 nodes

B. Problem Statement

We are interested in the following problem:

Optimal Swapping Order: For a given path of quantum nodes $\mathcal{V} = \{0, 1, ..., n\}$ with associated link capacity and elementary success probability $\{(c_{i-1,i}, p_{i-1,i})\}_{i=1}^{n}$ and node swapping probability $\{q_i\}_{i=1}^{n-1}$, find a swapping order that maximizes the path throughput.

Let us remark on the main challenges in dealing with this problem. First of all, it is the combinatoric nature of decisions, namely the swapping order, which has no counterpart in classical routing and forwarding. Specifically, in the case of heralded swapping, the number of possible swapping orders for a path scales exponentially with the number of routers. Second, as shown in (1)-(6), the expected throughput of a path is rather complicated, involving the characteristics of each node and every edge on the path as well as the swapping policy employed for the path. As a result, comparing two paths becomes nontrivial, especially when they have different link capacities, different lengths and different swapping policies, unless computation for the whole path is finished. However, computation complexity of the throughput in heralded swapping actually grows at a polynomial rate relative to the maximum width the path. As a result, solving the above problem exactly becomes impractical for a long path with high capacity. Most existing works often consider either a fixed swapping policy or order (e.g., [18], [5], [17]), or assume swapping time stays the same for all orders [7]. [10] considers a single-link setting and a different formulation using expected generation latency as their primary metric.

Here we focus on developing heuristic methods for static swapping. Our aim is to cope with practical issues raised above. Specifically, we provide efficient heuristics for scoring a swapping order, based on which we develop simple greedy algorithm for finding a good swapping policy.

Algorithm 1: ENT: Entanglement Throughput

Path: $\mathcal{P} = \{0, \ldots, n\}$, link capacity and prob. $(c_{x,x+1}, p_{x,x+1})$, swapping prob. q_x , swapping order \mathcal{O} $\mathcal{D} \leftarrow \left\{ \mathbf{p}(x, x+1) \right\}_{x=0}^{n-1}$ using (1) # distributions 2 for $s \in \mathcal{O}$ do $s^{l} \leftarrow \max\{x \in \mathcal{P} : x < s\} \ \ \text{\# predecessor}$ 3 $s^r \leftarrow \min\{x \in \mathcal{P} : x > s\} \ \# \ \text{successor}$ $S_s, \mathbf{p}(s^l, s^r) \leftarrow \text{SWAP}(\mathbf{p}(s^l, s), \mathbf{p}(s, s^r), q_s)$ 5 $\mathcal{P} \leftarrow \mathcal{P} \setminus \{s\}$ 6 $\mathcal{D} \leftarrow \mathcal{D} \setminus \{\mathbf{p}(s^l, s), \mathbf{p}(s, s^r)\} \cup \{\mathbf{p}(s^l, s^r)\}$ 7 8 return: S_s $SWAP(\mathbf{p}_1, \mathbf{p}_2, q)$: 9 $C_1 \leftarrow \operatorname{len}(\mathbf{p}_1), \quad C_2 \leftarrow \operatorname{len}(\mathbf{p}_2)$ 10 $C \leftarrow \min\{C_1, C_2\}, \quad \mathbf{p} \leftarrow \mathbf{0}_C$ 11 for k = 1, ..., C do for $i = k, ..., C_1$ do 12 13 $s \leftarrow 0$ for $j = k, ..., C_2$ do 14 $m \leftarrow \min\{j, i\}$ 15

 $s \leftarrow s + p_{2j} \times \binom{m}{k} q^k (1-q)^{m-k}$

17 $[p_k \leftarrow p_k + p_{1i} \times s]$ 18 $S \leftarrow \sum_k k \times p_k$ 19 return: (S, \mathbf{p})

16

IV. MAIN RESULTS

In this section, we first show how to estimate the path throughput efficiently and then provide a simple heuristic to deal with the number of possible swapping orders.

A. Evaluating Path Throughput

Algorithm 1 shows detailed steps for evaluating the expected number entanglements for any given swapping order. Let us now comment on the complexity of this algorithm. First, to optimize runtime, we can pre-compute and cache frequently used quantities, including $p_{i,i+1}^k$, $(1 - p_{i,i+1})^k$, q_i^k , $(1 - q_i)^k$, and binomial coefficients $\binom{c_{i,i+1}}{k}$ for all $k = 1 \dots, c_{i,i+1}$ and $i = 0, \dots, n-1$. This step requires $O(C^2)$ space and time with $C = \max\{c_{i,i+1}\}_{i=0}^{n-1}$. Given this, line 1 of Algorithm 1 using (1) only takes O(nC) but the most time-consuming of the algorithm is in the SWAP function, where each iteration of the inner-most loop performs O(1) operations and the nested loops take either $C_1^2C_2$ or $C_1C_2^2$ iterations. Thus, the worst-case complexity of this algorithm is $O(nC^3)$, which clearly does not scale well with capacity C. In the following, we introduce two approximations to deal with this complexity.

1) Approximating Distribution Tails: Note that the capacity c_{xy} of link (x, y) (both physical and virtual) is the support of the probability mass function of the entanglement distribution on this link. Although c_{xy} can be large, but $p_k(x, y)$ can actually be very small as k increases to c_{xy} . This is the case for physical links when the success probabilities of elementary link entanglements $p_{x,x+1}$ are small. Additionally, swapping with a small success rate q_y between E_{xy} and E_{yz} reduces $p_k(x, z)$ further compared to $p_k(x, y)$ and $p_k(y, z)$ for large k. This suggests that if $p := \max_x p_{x,x+1}$ is small, we can

Algorithm 2: Approximating Distribution Tail

 $\begin{array}{c|c} \operatorname{Approx}(\mathbf{p}, \epsilon):\\ \mathbf{i} \ t \leftarrow 0, \quad \tilde{\mathbf{p}}_{\epsilon} \leftarrow \mathbf{0}\\ \mathbf{2} \ \text{for} \ k = 0, \dots, \operatorname{len}(\mathbf{p}) - 1 \ \text{do}\\ \mathbf{3} & t \leftarrow t + p_k\\ \mathbf{4} & \text{if} \ t < 1 - \epsilon \ \text{then}\\ \mathbf{5} & & & \\ \mathbf{6} & & \\ \mathbf{7} & & & \\ \mathbf{7} & &$

improve the complexity significantly by reducing the support of any distribution up to a certain approximation error. One simple approach is to approximate the tail of each distribution function to an ϵ error as shown in Algorithm 2.

Note that Algorithm 2 runs at most linearly with the input size. Moreover, if $X \sim \mathcal{B}(C,p)$, then for K = O(Cp), Hoeffding's inequality yields the simple tail bound $\Pr(X \ge K) \le \exp(-2C(\frac{K}{C}-p)^2)$.³ Thus, by replacing all distributions in Algorithm 1 with their approximations, the worst-case complexity reduces to $O(nK^3) = O(np^3C^3)$ instead of $O(nC^3)$ as before.

2) Approximating Distributions: We now consider the case where C is large and the success probabilities of elementary link entanglements $p_{x,x+1}$ are not so small that the complexity order of $(Cp)^3$ can still be quite significant for the SWAP function in Algorithm 1. In this case, we introduce another approximation based on the following ideas:

• For a large C, a Binomial distribution $\mathcal{B}(C, p)$ can be reasonably approximated by a normal distribution, i.e.,

$$\mathcal{B}(C,p) \approx \mathcal{N}(Cp, Cp(1-p)) \tag{7}$$

when, e.g., the 3-standard-deviation condition holds, namely, C > 9 max{1-p/p, p/1-p}.
If min{E_{xy}, E_{yz}} can be approximated by a binomially

- If min{ E_{xy}, E_{yz} } can be approximated by a binomially distributed r.v., then so is E_{xz} .
- Assuming that q_y is not too small (which is practical as q = 0.5 can be achieved with linear optics) and the number of repeaters is not too large, we expect to have reasonable approximations even after all the swapping.

The above facts allow us to approximately switch between Binomial and Normal distributions and leverage the following result [16] on the exact moments of the minimum of two normal distributions.

Lemma 1. Let (X_1, X_2) be a bivariate Gaussian RV with means (μ_1, μ_2) , variances (σ_1^2, σ_2^2) , and correlation coefficient ρ . Define $\theta = \sqrt{\sigma_1^2 + \sigma_2^2 - 2\rho\sigma_1\sigma_2}$ and $\delta = \frac{\mu_2 - \mu_1}{\theta}$. Let $Y = \min\{X_1, X_2\}$. Then

$$\mathbb{E}\left[Y\right] = \mu_1 \Phi(\delta) + \mu_2 \Phi(-\delta) - \theta\phi(\delta) \tag{8}$$

$$\mathbb{E}[Y^{2}] = (\sigma_{1}^{2} + \mu_{1}^{2})\Phi(\delta) + (\sigma_{2}^{2} + \mu_{2}^{2})\Phi(-\delta) - (\mu_{1} + \mu_{2})\theta\phi(\delta),$$
(9)

³E.g., if
$$C = 10^3$$
, $p = 0.05$, $K = 2.5Cp$, this bound is 1.3×10^{-5} .

Algorithm 3: Swapping Normal Distributions

SWAP-N($(\mu_1, \sigma_1^2), (\mu_2, \sigma_2^2), q$): 1 $(\mu_Y, \sigma_Y^2) \leftarrow (8)-(9)$ using $(\mu_1, \sigma_1^2), (\mu_2, \sigma_2^2)$ 2 $(C_Y, p_Y) \leftarrow N2B(\mu_Y, \sigma_Y^2)$ 3 $(\mu, \sigma^2) \leftarrow B2N(C_Y, q \times p_Y)$ 4 return: (μ, σ^2) B2N(C, p): 5 $(\mu, \sigma^2) \leftarrow (Cp, Cp(1-p))$ 6 return: (μ, σ^2) N2B (μ, σ^2) : 7 $(C, p) \leftarrow (round(\frac{\mu^2}{\mu - \sigma^2}), 1 - \frac{\sigma^2}{\mu})$ 8 return: (C, p)

where $\phi(\cdot)$ and $\Phi(\cdot)$ are, respectively, the pdf and cdf of the standard normal distribution.

As a result, we propose to use normal distributions for approximating swapping outcomes as shown in Fig. 2, where the first, third and forth approximations are based on (7). The second approximation can work well if the two normal distributions are independent and do not have much overlap or when they have similar means and variances [16]. A significant benefit of these approximations is that instead of keeping track of all the distributions with possibly large supports (the same order as capacities), it is sufficient to just use the means and variances to characterize these normal distributions and perform calculations on these parameters. Detailed implementations are given in Algorithm 3, which takes only O(1) operations.



Fig. 2: Using normal distributions for approximating entanglement distribution and s-score. The mean and variance of Y, denoted by μ_Y and σ_Y^2 , are computed using (8)–(9) and (C_Y, p_Y) denote the parameters of approximated binomial distribution computed from (7). As a result, s-score of node v can be approximated by $C_Y p'_Y$, which is computed in O(1) time and space.

If we approximate all binomial distributions in Algorithm 1 by normal distributions (using $B2N(c_{x,x+1}, p_{x,x+1})$) and replace SWAP with SWAP-N in Algorithm 3, we do not even need to pre-compute all power terms and binomial coefficients as done before and the total complexity is just O(n), which is a significant reduction from $O(nC^3)$ and $O(np^3C^3)$. Of course, this advantage is not free as there are multiple approximation steps that only work well for certain ranges of C and p, such as the 3-standard-deviation conditions for (7). As a result, in our implementation, whenever such conditions are violated, we know that Cp is not large, we will switch back to using SWAP with distribution tail approximations. In this way, we can still keep the overall runtime as O(n).

B. Optimal Swapping Orders

As we demonstrated above, for each swapping order, the corresponding expected throughput can be computed or approximated efficiently. This means that if the total number of orders is not large, we can indeed find an optimal order by a brute force search that can benefit significantly from parallel computing.

Note that given a path of n + 1 nodes and n links, it has been shown [6], [7] that successive applications of swapping can be represented in terms of a full binary tree with leaves being quantum links and nodes being the quantum routers and the total number of trees is known as a Catalan number $T_{n-1} = 1, 2, 5, 14, 42, 132, 429, 1430, 4862, \ldots$ for $n \ge 2$ [19], [22]. Clearly, for small n, T_n remains relatively small; for example, we have 42 orders for n = 6, which we believe to be manageable for small scale networks. However, as nincreases, T_n increases exponentially, scaling asymptotically as $4^n/n^{1.5}$. In such cases, finding an optimal order using an exhaustive search is impractical, which calls for an efficient heuristic algorithm instead.

C. Heuristic Swapping Algorithms

We first define a scoring metric for nodes in path and then show how to use it to develop greedy heuristics.

1) Swapping Score: For any three nodes (x, y, z) that need not be adjacent neighbors, let us define a swapping score, or s-score, for node y as the expected number of (x, z)entanglements after swapping at node y, i.e.,

$$S_y = \mathbb{E}\left[E_{xz}\right] = \sum_k k \times p_k(x, z), \tag{10}$$

where $p_k(x, z)$ is given by (5). Here, it is important to note the following. First, the swapping score of node y depends on the left and right entanglements E_{xy} and E_{yz} , which are random variables and depend on the swapping order of the path. Second, as we demonstrated in the previous subsection, computing the score S_y can be done efficiently using SWAP with distribution tail approximations or SWAP-N using normal approximations. Third, the s-score of the last node in any swapping order \mathcal{O} is also the expected throughput ENT(\mathcal{O}) given in (6). Because of this, we will also refer to ENT(\mathcal{O}) as the *s-score* of swapping order \mathcal{O} .

2) Greedy Swapping: Having defined swapping scores for nodes in a path, we propose a simple greedy strategy for choosing a swapping order, namely, *swap with highest sscore first*. Here, the idea is to greedily select a node in the

Algorithm 4: GreedySwap
Path: $\mathcal{P} = \{0, \dots, n\}$, link capacity and prob.
$(c_{x,x+1}, p_{x,x+1})$, swapping prob. q_x
1 $\mathcal{O} \leftarrow \varnothing$
2 $\mathcal{D} \leftarrow \left\{ \mathbf{p}(x, x+1) \right\}_{x=0}^{n-1}$ using (1)
3 for $x = 1,, n - 1$ do
4 $ [S_x, \mathbf{p}(x-1, x+1) \leftarrow SWAP(\mathbf{p}(x-1, x), \mathbf{p}(x, x+1), q_x)] $
5 for $i = 1,, n - 1$ do
$6 s \leftarrow \arg \max \left\{ S_x : x \in \mathcal{P} \setminus \{0, n\} \right\}$
7 $\mathcal{O} \leftarrow \mathcal{O} \cup \{s\}$
$\mathbf{s} s^l \leftarrow \max\{x \in \mathcal{P} : x < s\}$
9 $s^r \leftarrow \min\{x \in \mathcal{P} : x > s\}$
10 $\mathcal{P} \leftarrow \mathcal{P} \setminus \{s\}$
$11 \mathcal{D} \leftarrow \mathcal{D} \setminus \{\mathbf{p}(s^l, s), \mathbf{p}(s, s^r)\} \cup \{\mathbf{p}(s^l, s^r)\}$
12 if $s^l > 0$ then
13 $s^{ll} \leftarrow \max\{x \in \mathcal{P} : x < s^l\}$
14 $S_{s^l}, \mathbf{p}(s^{ll}, s^r) \leftarrow \text{SWAP}(\mathbf{p}(s^{ll}, s^l), \mathbf{p}(s^l, s^r), q_{s^l})$
15 if $s^r < n$ then
$16 \qquad \qquad \qquad s^{rr} \leftarrow \min\{x \in \mathcal{P} : x > s^r\}$
17 $\left[S_{s^r}, \mathbf{p}(s^r, s^{rr}) \leftarrow \text{SWAP}(\mathbf{p}(s^l, s^r), \mathbf{p}(s^l, s^{rr}), q_{s^r}) \right]$
18 return : order \mathcal{O} , s-score S_s

path where its swaps result in highest expected number of entanglements, and then, once swapped, update the path and continue with this strategy.

We implement this greedy heuristic, which we call GreedySwap, in Algorithm 4 below. Specifically, starting with the initial path \mathcal{P} , we (i) compute the s-scores of all the nodes (lines 2-4), (ii) find one node s with the highest score to swap (lines 5-7), identify its left and right neighbors in \mathcal{P} (lines 8-9), remove it from the path (line 10), (iii) find the entanglement distribution of the new logical link (s^l, s^r) , update entanglement distributions of the modified path and then go back to step (i) until there is no more node left to swap. Note that after swapping at node s, only s-scores of its left and right neighbors (s^l, s^r) according to the swapping order need to be updated; these neighbors can be different from immediate neighbors in the physical topology. We employ this fact in updating entanglement distributions of the path (lines 12-17). Thus, compared to Algorithm 1 which takes (n-1) SWAP calls, GreedySwap incurs no more than 3(n-1) calls. As a result, both algorithms have similar runtime complexity, i.e., GreedySwap enjoys all efficient approximations developed in section IV-A.

Note that being a greedy heuristic, Algorithm 4 can sometimes provide suboptimal orders instead. We leave a rigorous analysis for future work, but provide here a simple example showing when it can or cannot find an optimal order.

Example 2: Consider again the network with 5 nodes in Fig. 1 with elementary entanglement success rates $p_{i,i+1} = 0.2, \forall i = 0, \ldots, 3$ and swapping success rates $q_j = 0.5$ for j = 1, 2, 3. If the link capacities are $c_{01} = 100, c_{12} = 200, c_{23} = 300$ and $c_{34} = 400$, the GreedySwap correctly finds the optimal order, which is [3, 2, 1] with an s-score of 7.16. Now if instead, the capacities are $c_{01} = 100, c_{12} = 101, c_{23} = 101$

Algorithm 5: VoraSwap

Path: $\mathcal{P} = \{0, \dots, n\}$, link capacity and prob. $(c_{x,x+1}, p_{x,x+1})$, swapping prob. q_x 1 $\mathcal{O}_{grd}, S_{grd} \leftarrow \text{GreedySwap}$ 2 $\mathcal{O}_{bal} \leftarrow \text{BalancedTree}(\mathcal{P})$ 3 $S_{bal} \leftarrow \text{ENT}(\mathcal{O}_{bal})$ 4 return: $(\mathcal{O}_{grd}, S_{grd})$ if $S_{grd} > S_{bal}$ else $(\mathcal{O}_{bal}, S_{bal})$

and $c_{34} = 100$, then GreedySwap will pick node 2 first and yield the order [2, 1, 3] with an s-score of 2.24 whereas the balanced tree gives the highest score of ENT([1, 3, 2]) = 3.72 and sequential orders achieves the lowest: ENT([1, 2, 3]) = ENT([3, 2, 1]) = 2.23.

Our observation is that if the path is very heterogeneous, GreedySwap can often find a good (even optimal) swapping order. It might be less effective for paths that are close to homogeneous, where we know a balanced tree will likely to perform well. Based on this, we propose a simple heuristic combining these two cases, which we call *voracious swapping* or VoraSwap as shown in Algorithm 5, where the s-score of GreedySwap is compared against that of a balanced tree. This algorithm has the same complexity as GreedySwap.

D. Optimal Resource Allocation

In this subsection, we present an interesting application of our model and algorithms developed above, namely optimal allocation of path capacity.

We assume that each node i in the path has a finite memory, denoted by Q_i . To generate elementary link entanglements, two adjacent nodes i and i+1 must allocate the same number of memories, denoted by m_i , which satisfies

$$1 \le m_i \le \min\{Q_i, Q_{i+1}\}$$

Clearly, the capacity $c_{i,i+1}$ is an increasing function of m_i , which could be nonlinear depending on quantum and classical channel frequencies, rate count and resolution of detectors, efficiency of memory management among other factors. Note that when these frequencies and resolutions are high enough and the number of memory is not too large, then it is reasonable to approximate this relation by a linear function. We will validate this point later in the simulation section below. We are interested in the following problem:

Link memory allocation: Given memory capacities of the nodes in the path, how to allocate them to each link to maximize the path throughput.

This problem is related to our main problem **Optimal Swapping Order** above because, when link capacities change, the optimal swapping order is likely to change. Mathematically, we want to solve the following integer optimization:

$$\max_{\mathbf{m},\mathcal{O}} \quad \text{ENT}(\mathbf{m},\mathcal{O}) \tag{11}$$

s.t. $m_i \in \{1, 2, \dots, Q_i\}, \quad i = 0, \dots, n$ (12)

$$m_{i-1} + m_i \le Q_i, \quad i = 1, \dots, n-1.$$
 (13)

Clearly, solving this problem exactly is even harder than finding an optimal swapping order because of an additional layer of hardness in the integer-constraints of the memory allocations. We leave finding an efficient algorithm for solving this problem as future work but note here a heuristic that is amenable to scenarios where nodes have small memory capacity. Specifically, as the s-score as well as throughput is increasing in the capacity of the links, an optimal memory allocation will be at an extreme point of the constraint set. As a result, we can apply our greedy swapping heuristic at all the extreme points and find one with highest swapping score.

V. SIMULATION AND EVALUATION

In this section, we will evaluate our algorithms using an open-source simulator called SeQUeNCe [23], a discrete-event simulator of quantum networks. The general simulation setup is given in subsection V-A. We will discuss the applicability of our model in subsection V-B through a detailed simulation of a simple path with three nodes. We will then consider a longer path with 6 nodes in subsection V-C. Finally, subsection V-D presents further simulation results for paths with different number of nodes and varying distances between them.

A. Setup

We use the following parameters as default unless specified otherwise. Each node has a quantum memory capacity between 2 and 6. Quantum memories have efficiency of 0.95 and frequency of 1 kHz. We will vary the coherence time between 2 ms, 5 ms, 10 ms, 20 ms and up to 100 ms in some cases. Quantum channels are fibers with a peak frequency of 50 MHz and an attenuation rate of 0.2 dB/km. The speed of light in fiber is $c_0 = 2 \times 10^5$ km/s. We assume photon detectors have a count rate of 60 MHz with 100 ps time-resolution and 0.95 efficiency. The success rate of swapping is 0.5 for every node. Finally, in each experiment in SeQUeNCe, the simulation duration is set to last 9 seconds or until 1000 E2E entanglements is reached.

B. Applicability of Our Model

Although SeQUeNCe is a discrete-event simulator and it does not rely on the notion of a time-slot, our modeling approach can still offer a reasonable approximation for studying swapping orders and path throughput because of the following. First, for elementary entanglement generation, SeQUeNCe uses Barrett-Kok protocol [2] with time-division multiplexing [20] to support multiple attempts "simultaneously" and continuously as long as there are available memory. Given that each memory-pair will require a lot of attempts to generate an entanglement, the heralding signal latency will be relatively small compared to the duration of entanglement generation phase. This is similar to our assumption regarding the external phase for continuous entanglement generation and internal phase for swapping and signaling. Second, in SeQUeNCe implementations, entanglement swapping happens whenever two entanglements are available and satisfy swapping rules and conditions, reducing the wait time of entangled qubits in the memory. Our swapping model can also approximate this mechanism because to perform swaps in (3), any pair of



Fig. 3: Three node path with different distances.



Fig. 4: Link evaluation with varying number of assigned memory pairs. *Left:* number of attempts per second; *Middle:* number of entanglements per second; *Right:* fraction of successful attempts.

entangled qubits in memory can be used, which means that, in terms of throughput, the order of these swaps at a node in a time slot should not matter. We will demonstrate this through a detailed experiment with a three-node path with distances: $L_1 = 32$ km and $L_2 = 18$ km shown in Fig. 3.

1) Estimating Link Capacity: We first evaluate each link separately in isolation by assigning M = 1, ..., 5 memory pairs for each link and running 1000 experiments in each case with the simulation duration set to 1 second. Fig. 4 shows the number of attempts per second (A_i) , the number of generated entanglements per second (E_i) and the success rate (r_i) from these experiments.

As we can see, given a sufficiently large count rate of detector and frequency of quantum channels, the attempt rate and entanglement rate increase linearly with the number of memory pairs assigned to each link. Second, the shorter link not only has a higher attempt rate but also has a much higher success rate. Third, although each attempt of the Barrett-Kok protocol can take either 3 or 4 times the link latency [2], [23], we can still reasonably approximate the entanglement rate and success rate as its parameters. Fig. 5 shows the histogram of entanglement rates and the probability mass function of the approximated Binomial variables.

2) Estimating Swapping Throughput: We now consider swapping of the two entanglement distributions when putting two links together. Let us first consider the case with M = 1memory pair assigned to each link. To select a time slot for our model, consider the following approximations. Let T_i be the random variable representing the time each link takes to generate one new entanglement (after a swap). Clearly, a swap is only possible if there are entanglements on both links and they must be created not more than a certain time apart. Let $T_{\rm cutoff}$ denote this cutoff time, which depends on the coherence time of memory, the delay in heralding swapping results to the end nodes $\tau_{\rm her} = \max{\{L_i\}/c_0}$ and the delay in



Fig. 5: Histogram of entanglement rates (over 1000 runs) and the probability mass functions of the approximated Binomial random variables when 1 pair of memory is assigned to each link.

consuming the end-to-end entanglement by applications τ_{app} if succeeded, i.e., $T_{cutoff} := T_{cohere} - \tau_{her} - \tau_{app}$. Here, in this example, we assume that $\tau_{her} + \tau_{app} \ll T_{cohere}$ so that $T_{cutoff} \approx T_{cohere}$. Note that if T_{cohere} is sufficiently large compared to T_i , then one entanglement once established can just wait for the other to become available to swap, which takes $T_{12} := \max\{T_1, T_2\}$. On the other hand, when T_{cohere} is small in relation to T_{12} , then T_{cutoff} will be small, so one entanglement is likely to decohere and must be restarted (possibly multiple times) before the other one become available. Based on this, we propose to select a time slot as

$$T_s = \min \left\{ \mathbb{E}[T_{12}], T_{\text{cutoff}} \right\}.$$

Since the entanglement rate E_i of link *i* is well approximated by a Binomial random variable as shown above, we can approximate T_i by an exponentially distributed variable with rate $\frac{1}{\mathbb{R}[E_i]}$ and find

$$\mathbb{E}[T_{12}] \approx \frac{1}{\mathbb{E}[E_1]} + \frac{1}{\mathbb{E}[E_2]} - \frac{1}{\mathbb{E}[E_1] + \mathbb{E}[E_2]}.$$

Once T_s is selected, we can find capacity of each link i as $C_i = \operatorname{round}(\mathbb{E}[A_i] \times T_s)$ and the success probability of each attempt as $p_i = \mathbb{E}[r_i]$ and then proceed with our Algorithm 1 to find s-score S_1 of node 1. Note that since our model only accepts C_i as an integer, a rounding step is needed, which might cause non-negligible additional approximation errors when C_i is small. Finally, the estimated throughput (in E2E entanglements per second) will be ENT = $S_1/(T_s + \tau_{her} + \tau_{app}) \approx S_1/T_s$ assuming $\tau_{her} + \tau_{app} \ll T_s$.

Fig. 6 below demonstrates that the estimated throughput using our model matches rather well with the simulation results (mostly within 1-standard-deviation over 1000 runs) for different values of the coherence time $T_{\rm cohere}$, ranging from 2 ms to 100 ms. As expected, the throughput does not change much for large coherence times but reduces significantly as $T_{\rm cohere}$ becomes small.

3) Link Memory Allocation: Next, consider the case where each node in the path has a fixed number of memories $Q_i = 6$ so that each link can be assigned more than a single memory pair. As we showed in Fig. 4 above, assigning more memory



Fig. 6: Comparison of estimated throughput using our model with simulation results (over 1000 runs) for different values of the coherence time T_{cohere} . Here, M = 1 memory pair assigned to each link.

pair to each link will increase its entanglement generation rate linearly. Since the two links are quite different, it is more beneficial to assign more memory to the longer link. We are interested in finding which allocation profile will give the highest throughput. Fig. 7 shows the estimated throughput using our model and the simulation results (over 1000 runs) for different values of the coherence time T_{cohere} and different memory allocation $\mathbf{m} = [m_1, m_2]$. We note the following:

- Compared to the case with $\mathbf{m} = [1, 1]$ shown in Fig. 6, by increasing the memory assignment, the throughput not only increases significantly but also is more stable across different values of coherence time. This is mainly because higher entanglement rates on either link reduce the wait time of entangled qubits in memory, thereby tolerating a lower cutoff time while increasing the throughput.
- Since entanglement rate of L_1 is much lower (more than 3 times) than that of L_2 when $\mathbf{m} = [1, 1]$, the throughput is largely affected by L_1 . This will roughly hold the same for any allocation of memory $\mathbf{m} = [m_1, m_2]$ with $m_1 \le m_2$, which explains the linear part of the plots in Fig. 7. As more capacity is shifted from L_2 to L_1 , the difference in the rates of both links reduces and the allocation $\mathbf{m} = [4, 2]$ actually achieves the highest throughput.
- Most importantly, our model consistently and efficiently predicts well the throughput of the path for differently coherence times and memory allocations and thus correctly identifies the optimal resource allocation. This proves the validity and applicability of our model.



Fig. 7: Comparison of the estimated throughput using our model with the simulation results (averaged over 1000 runs) for different values of the coherence time T_{cohere} and different memory allocation m.



Fig. 8: Path with 6 nodes in the DC metro area.

C. Example of a 6-Node Path

Consider a longer path with 6 nodes with their distances shown in Fig. 8 below. Suppose that each node has a memory capacity of $Q_i = 6$. We are interested in finding the maximum end-to-end entanglement throughput that this path can support.

We will compare our approach with the following swapping orders: baln = [1,3,2,4], bal2 = [4,2,3,1], L2R = [1,2,3,4] and R2L = [4,3,2,1]. Here baln and bal2 are two doubling orders (a.k.a., balanced trees) whereas L2R and R2L are sequential orders. Additionally, we also implemented the swap-asap policy, denoted by asap, which does not have a fixed order as entanglements are swapped as soon as possible. For our model, we simply take $T_s = T_{cohere} - \tau_{rtt}$ where $\tau_{rtt} = 2\frac{L_{0.5}}{c_0}$ is the round trip time approximating the heralding delay. The order found by our algorithm is denoted by vora.

Fig. 9 shows the throughput of different swapping orders with two different link memory allocations when varying the coherence time. In all cases, our heuristic algorithm outputs vora = [4, 1, 3, 2], which is also the optimal order, and optimal memory allocation $\mathbf{m} = [4, 2, 4, 2, 4]$. The blue dashline is the estimated rate from our model, which follows reasonably well with simulation results of vora, confirming the effectiveness of our approach. Finally, we note that our algorithms are very efficient, e.g., on a machine with Intel(R) Core(TM) i9-3.20 GHz, for $T_{cohere} = 20$ ms, GreedySwap takes about 200 ms to find a score of 59.72, GreedySwap using tail distribution approximations with $\epsilon = 10^{-5}$ takes 13 ms to find a score of 59.72, whereas with normal distribution approximations, it estimates a score of 58.69 in only 2 ms.



Fig. 9: Throughput of different swapping policies when varying coherence time in two memory allocations. The dash blue line shows our model's estimates while other lines are the average of 100 runs.

D. Further Experiments

In this subsection, we present further evaluations of our approach against the following policies: baln, L2R, and asap. We fix the end-to-end distance of the path at 150 km, but vary the number of repeaters to be 3, 4, 5 and consider the



Fig. 10: Comparison of entanglement rates across different network sizes with 3, 4, and 5 routers; vora orders also shown in the plots.



Fig. 11: Comparison of the number of expired memories per entanglement across different network sizes: 3, 4, and 5 routers.

distances among them allocated according to the following scenarios: (i) Uniform: all quantum channels have the same length; (ii) Increasing: linearly so that link (i, i + 1) distance is $(2i+1)d_0$ for i = 0, ..., n, where the normalizing constant d_0 is also the length of link (0, 1); (iii) Decreasing: the reverse of Increasing; and (iv) Mid-bottleneck: all channels have the same length except for the middle channel(s), which is (are) 1.2 times longer than others. In all cases, we assign 25 memory pairs for each link and set $T_{cohere} = 10$ ms. Due to a large number of settings, we repeat each case 30 times and in each experiment, the simulation duration is set to last 20 seconds or until 200 E2E entanglements is reached. We report in Fig. 10 the throughput of the considered swapping policies and in Fig. 11 their resource efficiency in terms of the number of expired memories per E2E entanglement generated.

We have the following observations. First, vora overall outperforms other policies in both throughput and memory efficiency; in some cases, vora coincides with either L2R (3router with increasing distances) or baln (3-router with Midbottleneck or uniform distances) as they are optimal orders. Second, L2R only performs well with increasing distances, which is to be expected as it can utilize entanglements better compared to other distance allocations – obviously, it performs the worst with decreasing distances. Third, baln generally performs reasonably well under symmetric distance distributions (Uniform and Mid_bottleneck), particularly for the 3-router case where the swapping tree is perfectly balanced. However, in cases with 4 and 5 routers, vora gives better orders. Fourth, asap performs fairly consistent across different distance distributions; it works best in the Uniform case. Generally, asap is better than L2R (except for case with increasing distances) but worse than baln and vora, especially when the number of routers increases. Its greedy and locally-driven swapping behavior results in such inefficiency.

These findings emphasize the impact of both the network topology and the structure of the swapping strategy on overall performance, showcasing the effectiveness of our approach in finding optimal swapping orders.

VI. CONCLUSIONS

In this paper, we considered the problem of finding optimal swapping orders in a heterogeneous path of quantum repeaters so as to maximize the end-to-end entanglement throughput. As the complexity of determining path throughput grows at a cubic rate relative to the link capacities and the number of swapping orders scales exponentially with the number of repeaters, we develop efficient heuristics for finding a good swapping order that run only linear in the path length. We demonstrated the flexibility and applicability of our model as well as the effectiveness of our heuristics through simulations in a discrete-event quantum network simulator. Our future work will focus on incorporating fidelity constraints and purification steps in finding swapping orders in a path and multi-path. Using our model and heuristics for entanglement routing in more general network topologies with multiple users will also be important next steps.

REFERENCES

 Amar Abane, Michael Cubeddu, Van Sy Mai, and Abdella Battou. Entanglement routing in quantum networks: A comprehensive survey. *IEEE Transactions on Quantum Engineering*, 6:1–39, 2025.

- [2] Sean D. Barrett and Pieter Kok. Efficient high-fidelity quantum computation using matter qubits and linear optics. *Phys. Rev. A*, 71:060310, Jun 2005.
- [3] H.-J. Briegel, W. Dür, J. I. Cirac, and P. Zoller. Quantum repeaters: The role of imperfect local operations in quantum communication. *Phys. Rev. Lett.*, 81:5932–5935, Dec 1998.
- [4] H-J Briegel, Wolfgang Dür, Juan I Cirac, and Peter Zoller. Quantum repeaters: the role of imperfect local operations in quantum communication. *Physical Review Letters*, 81(26):5932, 1998.
- [5] Marcello Caleffi. Optimal routing for quantum networks. *IEEE Access*, 5:22299–22312, 2017.
- [6] Kaushik Chakraborty, David Elkouss, Bruno Rijsman, and Stephanie Wehner. Entanglement distribution in a quantum network: A multicommodity flow-based approach. *IEEE Transactions on Quantum Engineering*, 1:1–21, 2020.
- [7] Alena Chang and Guoliang Xue. Order matters: On the impact of swapping order on an entanglement path in a quantum network. In IEEE INFOCOM 2022-IEEE Conference on Computer Communications Workshops (INFOCOM WKSHPS), pages 1–6. IEEE, 2022.
- [8] W. Dür, H.-J. Briegel, J. I. Cirac, and P. Zoller. Quantum repeaters based on entanglement purification. *Phys. Rev. A*, 59:169–181, Jan 1999.
- [9] Ali Farahbakhsh and Chen Feng. Opportunistic routing in quantum networks. In *IEEE INFOCOM 2022-IEEE Conference on Computer Communications*, pages 490–499. IEEE, 2022.
- [10] Mohammad Ghaderibaneh, Caitao Zhan, Himanshu Gupta, and CR Ramakrishnan. Efficient quantum network communication using optimized entanglement swapping trees. *IEEE Transactions on Quantum Engineering*, 3:1–20, 2022.
- [11] Stav Haldar, Pratik J Barge, Xiang Cheng, Kai-Chi Chang, Brian T Kirby, Sumeet Khatri, Chee Wei Wong, and Hwang Lee. Reducing classical communication costs in multiplexed quantum repeaters using hardware-aware quasi-local policies. *Communications Physics*, 8(1):132, 2025.
- [12] Stav Haldar, Pratik J Barge, Sumeet Khatri, and Hwang Lee. Fast and reliable entanglement distribution with quantum repeaters: principles for improving protocols using reinforcement learning. *Physical Review Applied*, 21(2):024041, 2024.
- [13] Lars Kamin, Evgeny Shchukin, Frank Schmidt, and Peter van Loock. Exact rate analysis for quantum repeaters with imperfect memories and entanglement swapping as soon as possible. *Physical Review Research*, 5(2):023086, 2023.
- [14] Vinay Kumar, Claudio Cicconetti, Marco Conti, and Andrea Passarella. Routing in quantum repeater networks with mixed noise figures, 2023.
- [15] Jian Li, Qidong Jia, Kaiping Xue, David SL Wei, and Nenghai Yu. A connection-oriented entanglement distribution design in quantum networks. *IEEE Transactions on Quantum Engineering*, 3:1–13, 2022.
- [16] Saralees Nadarajah and Samuel Kotz. Exact distribution of the max/min of two gaussian random variables. *IEEE Transactions on very large scale integration (VLSI) systems*, 16(2):210–212, 2008.
- [17] Mihir Pant, Hari Krovi, Don Towsley, Leandros Tassiulas, Liang Jiang, Prithwish Basu, Dirk Englund, and Saikat Guha. Routing entanglement in the quantum internet. *npj Quantum Information*, 5(1):25, 2019.
- [18] Shouqian Shi and Chen Qian. Concurrent entanglement routing for quantum networks: Model and designs. In Proceedings of the Annual conference of the ACM Special Interest Group on Data Communication on the applications, technologies, architectures, and protocols for computer communication, pages 62–75, 2020.
- [19] Richard P Stanley. Catalan numbers. Cambridge University Press, 2015.
- [20] Suzanne B van Dam, Peter C Humphreys, Filip Rozpedek, Stephanie Wehner, and Ronald Hanson. Multiplexed entanglement generation over quantum networks using multi-qubit nodes. *Quantum Science and Technology*, 2(3):034002, 2017.
- [21] Rodney Van Meter, Takahiko Satoh, Thaddeus D Ladd, William J Munro, and Kae Nemoto. Path selection for quantum repeater networks. *Networking Science*, 3:82–95, 2013.
- [22] Wikipedia. Catalan number, 2025. [Online; accessed 1-April-2025 at https://en.wikipedia.org/wiki/Catalan_number].
- [23] Xiaoliang Wu, Alexander Kolar, Joaquin Chung, Dong Jin, Tian Zhong, Rajkumar Kettimuthu, and Martin Suchara. SeQUeNCe: a customizable discrete-event simulator of quantum networks. *Quantum Science and Technology*, 6(4):045027, 2021.